



Iss.		Date	Modification	Ckd.	Appd.
3	07.07 2014	No issue 2 drawing, up-issued from 1 to 3.	Length (behind panel) was 74	.	.
4	17.12 2014	Corrected optional customer tag position and added note to skip issue 2.			
5	10.05 2017	CRN1652: Panel cut-out updated. CRN1617 Rubber cap added.			


**BEKA** associates  
Hitchin  
England  
company confidential, copyright reserved.



VIEW ON ARROW A  
(REAR PANEL DETAILS)




TERMINAL CONNECTIONS:



INSTALLATION:

- 1 INSERT UNIT INTO PANEL CUTOUT FROM FRONT.
- 2 SCREW CLAMPS ARE FITTED OVER THE 4 STUDS & THE WING NUTS TIGHTENED FROM REAR OF PANEL. RECOMMENDED TORQUE 22cNm MIN.
- 3 FOR PANELS GREATER THAN 3mm THICK ADD ADDITIONAL DEPTH FOR CLAMPS. (ie ADD PANEL THICKNESS LESS 3mm)
- 4 FINALLY, FIT A SILICONE RUBBER CAP TO THE END OF EACH M3 THREADED ROD.



Title  
CUSTOMER DRAWING for  
BA307NE 4 DIGIT INDICATOR  
IN PANEL MOUNTING ENCLOSURE

Drawn RC  
Checked .  
Scale NTS  
Drawing No. CD307NE