



Iss.	1	2
Date	16.12 2014	10.05 2017
Modification	First release under project P0170.	CRN1652 Panel cut-out updated. CRN1617 Rubber cap added.
Ckd.		
Appd.		
Iss.	3	
Date	15.05 2019	
Modification	CRN1791. Remove reference to I.S.	
Ckd.		
Appd.		


BEKA associates
Hitchin
England
company confidential, copyright reserved.



VIEW ON ARROW A
(REAR PANEL DETAILS)




TERMINAL CONNECTIONS:



INSTALLATION:

- 1 INSERT UNIT INTO PANEL CUTOUT FROM FRONT.
- 2 SCREW CLAMPS ARE FITTED OVER THE 4 STUDS & THE WING NUTS TIGHTENED FROM REAR OF PANEL. RECOMMENDED TORQUE 22cNm MIN.
- 3 FOR PANELS GREATER THAN 3mm THICK ADD ADDITIONAL DEPTH FOR CLAMPS. (ie ADD PANEL THICKNESS LESS 3mm)
- 4 FINALLY, FIT A SILICONE RUBBER CAP TO THE END OF EACH M3 THREADED ROD.



Title
CUSTOMER DRAWING for
BA527E-SS 5 DIGIT INDICATOR
IN PANEL MOUNTING ENCLOSURE

Drawn	Checked	Scale
KB	.	NTS
Drawing No.		CD527E-SS