




THIRD ANGLE PROJECTION


DIMENSIONS IN mm

DO NOT SCALE



MOUNTING DIMENSIONS:
4 OFF $\phi 6.5$ mm CLEARANCE HOLES
SUITABLE FOR SCREWS WITH HEAD $\phi 10$ mm MAX.
(M5 PAN HEAD OR M6 CHEESE HEAD)

VIEWS OF REAR CASE WITH FRONT REMOVED



TERMINALS 2 & 4
INTERNALLY LINKED FOR
JOINING RETURN 4/20mA WIRE

TERMINALS 5 & 6
INTERNALLY LINKED FOR
JOINING CABLE SCREENS

EACH TERMINAL CAN ACCOMMODATE ONE 0.2 – 2.5mm² SOLID CONDUCTOR
OR
ONE 0.2 – 1.5mm² STRANDED CONDUCTOR

1	08.10 2019	P0179. First release.		
Iss.	Date	Modification	Ckd.	Appd.

BEKA associates
Hitchin England
company confidential, copyright reserved.

Title
CUSTOMER DRAWING for
BA304SG 4 DIGIT Ex eb & tb INDICATOR
IN FIELD MOUNTING ENCLOSURE

Drawn RH	Checked .	Scale N/A
Drawing No. Sheet 1 of 1		CD304SG