


Iss.	1	Date	24.11 2011	Modification		Appd.	
Iss.		Date		Modification		Appd.	
BEMA associates Hitchin England company confidential, copyright reserved.							
Iss.		Date		Modification		Appd.	
Ckd.		Date		Modification		Appd.	






THIRD ANGLE PROJECTION

DIMENSIONS IN mm

DO NOT SCALE


* IF TAG OR SCALE INFORMATION IS NOT SUPPLIED THESE WILL BE LEFT BLANK.




CARBON LOADED GLASS REINFORCED POLYESTER (GRP) ENCLOSURE.

MOUNTING DIMENSIONS:
2 off M6 CLEARANCE HOLES SUITABLE FOR SCREW WITH HEAD DIAMETER 12 MAX


TERMINAL CONNECTIONS:



ENCLOSURE WITH TERMINAL AND CONTROL COVERS REMOVED



SCREENS SEE NOTE 2



TERMINAL INTERNALLY CONNECTED TO RFI SCREEN OF ENCLOSURE

NOTES:

- 1 TERMINALS 2 & 4 ARE INTERNALLY LINKED FOR JOINING RETURN WIRES
- 2 TERMINALS 5 & 6 ARE INTERNALLY LINKED FOR JOINING CABLE SCREENS

Title CUSTOMER DRAWING for
BA354E LOOP POWERED RATE TOTALISER
IN FIELD MOUNTING ENCLOSURE

Drawn RC	Checked .	Scale NTS
Drawing No.		CD354E