



IF TAG OR SCALE INFORMATION IS NOT SUPPLIED THESE
- WILL BE LEFT BLANK

DISPLAY
-HEIGHT 34mm

CARBON LOADED
- SILICONE RUBBER KEYPAD

STAINLESS STEEL
GRADE ANC4B
(A4/316)
ENCLOSURE

-ENCLOSURE FRONT

-ENCLOSURE REAR

2 OFF
M20 x 1.5
CONDUIT ENTRIES

OPTIONAL ALARM TERMINALS

OPTIONAL
BACKLIGHT
TERMINALS

TERMINAL CONNECTIONS:

UNIT
TERMINALS

TERMINAL SCREWS

CABLE -ENTRIES

11 -	ALARM 2	INPUT 4-20 mA	2-
10 +			<-3
		2 & 4 LINKED	4-
9 -			
8 +	ALARM 1		
14 -	SEPARATELY POWERED		
13 -	LOOP POWERED		
12 +	COMMON		

84

19. 90

106

MOUNTING DIMENSIONS:
4 OFF $\phi 6.5\text{mm}$ CLEARANCE HOLES
SUITABLE FOR SCREWS WITH HEAD $\phi 10\text{mm}$ MAX.
(M5 PAN HEAD OR M6 CHEESE HEAD)

REMOVABLE
TERMINAL BLOCKS

OPTIONAL

OPTIONAL

UNIT
— TERMINALS

SLIDE IN
SCALE CARD
FOR INTERNAL
TAG & SCALE
— INFORMATION

REAR VIEW OF FRONT
SHOWING TERMINAL CONNECTIONS
ALARM & BACKLIGHT ARE OPTIONAL

VIEW OF REAR CASE WITH FRONT REMOVED

ISOLATED
SCREEN
STUD M4

ENCLOSURE
EARTH
SCREW

NOTE:
TERMINALS 2 & 4 ARE INTERNALLY LINKED FOR JOINING RETURN WIRES.

Title	CUSTOMER DRAWING for BA504G-SS 4 DIGIT INDICATOR IN FIELD MOUNTING ENCLOSURE	Drawn	Checked	Scale
		KB	.	N/A
		Drawing No. CD504G-SS		
		Sheet 1 of 1		